VA1913wm

19" (18.5" VIEWABLE)
16:9 WIDESCREEN LCD

WITH 10,000:1 DYNAMIC CONTRAST RATIO

Widescreen for work and play

ViewSonic's 19" VA1913wm 16:9 widescreen features automatic aspect ratio adjustment that ensures a full, undistorted screen image. High brightness and fast video response deliver brilliant, blur-free images, while the ultra-high 10,000:1 dynamic contrast ratio produces greater detail and definition especially in darker images. This multimedia monitor features invisible, integrated stereo speakers to complement gaming, video viewing and Internet activity with rich stereo sound. Eco-mode automatically conserves power when not in use. The VA1913wm is the right choice for home/small office users, students, gamers and corporate professionals.

Work faster. Play more.

> **Widescreen aspect ratio with 1366 x 768resolution**
The widescreen aspect ratio allows you to view HD content in its native format with no stretching or distortion.

> **10000:1 Dynamic Contrast Ratio**
Provides darker black levels and better overall front-of-screen performance.

> **ClearMotiv® 5ms video response time**
Fast 5ms video response enables digital HD broadcast-quality video.

> **Multimedia enhanced**
Save desk and workspace and enjoy rich, stereo sound with built-in 2Wx2 stereo speakers.

> **ECO Mode**
Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.

> **Aspect ratio adjustment**
Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference™

VA1913wm

ViewSonic®
See the difference™

19” widescreen LCD with 10,000:1 dynamic contrast ratio

Model No.VS12293 (VA1913wm-2)
VS12294 (VA1913wm-4)

LCD	Size	18.5" wide Color TFT Active Matrix LCD 16:9 aspect ratio
	Display Area	409.8mm (H) × 230.4mm(V)
	Optimum Resolution	1366×768
	Brightness	300 cd/m² (Typ.)
	Contrast Ratio	1000:1 (Typ.)
	Dynamic Contrast Ratio	10000:1
	Viewing Angles	170° (H), 160° (V)(CR≧10)
	Response Time	5ms
	Pixel Pitch	0.3mm (H)×0.3mm (V)
	Panel Surface	Anti-Glare, Hard coating (3H)
	Light Source	50,000 hrs (Typ.)
	Color Support	16.7 M (6-bits + Hi FRC) Panel
INPUT	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)
	Sync	Separate Sync
	Frequency	Fh: 24-82kHz, Fv: 50-85Hz
COMPATIBILITY	PC	VGA up to 1366×768 Non Interlaced
	Mac	Power Mac, up to 1366×768
CONNECTOR	Analog	15 pin mini D-sub×1
	Audio	3.5 mm Audio line-in
	Power	Built-in power Adapter, 3-Pin plug
AUDIO	Speaker	2W X 2
POWER	Voltage	AC 100-240V (Universal); 50/60Hz(Switch)
	Consumption	23W (Max.)
	Eco Mode	optimize 18W / conserve 15W
	Save mode (W)	≦1W
ERGONOMICS	Tilt	20° ~ -5°
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView	Auto Image Adjust, Contrast/Brightness, Audio adjust (Volume, mute) Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]), Information, Manual Image Adjust (Horizontal Size, H/V Position, Fine Tune, Sharpness, Dynami
OPERATING CONDITIONS	Temperature	5°C - 35°C (41°F - 95°F)
	Humidity	20 - 80% (Non condensed)
DIMENSIONS (WXHXD)	Physical (w/ stand)	447 × 350 × 199 (mm), 17.6 × 13.8 × 7.8 (in)
	Physical (w/o stand)	447 × 268 × 63(mm), 17.6 × 10.6 × 2.46 (in)
WEIGHT	Net	3.4 kg (7.5lbs)
REGULATIONS		CB, TCO'03, WEEE, ROHS, UL/cUL, FCC-B, IRAM, NOM, Energy Star, ERGO, CE, Ukraine, GOST-R+Hygienic, SASO, BSMI, PSB, C-TICK, MIC, VCCI, CCC
WALL MOUNT		VESA 100mm x 100mm

Rev.1c

ISO 9001:2000 FM 40187
ISO 14001:1996 FM 40968

ViewSonic Corporation`s QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Headquarters:
381 Brea Canyon Road,
Walnut, CA 97189, U.S.A.
salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific:
9F, No. 1 92 Lien Chien Road,
Chung Ho, Taipei, R.O.C.
www.viewsonic.com.tw

ViewSonic Singapore:
Marine Parade Road #09-02
Parkway Parade
Singapore 449269
www.viewsonic.com.sg

ViewSonic Australia:
Unit 4, 44 Dickson Ave, Artarmon
NSW 2064, Australia
www.viewsonic.com.au

ViewSonic Korea:
#2110, 21F, Renaissance Tower Bldg.,
456 Gongdeok-dong, Mapo-gu, Seoul,
121-020, Korea
www.kr.viewsonic.com

ViewSonic India:
Unit No.2, 3 & 4 (Ground Floor),
Tribhuvan Complex,
Ishwar Nagar, Mathura Road,
New Delhi – 110065
in.viewsonic.com